


PRELUDE 15 XL²

Exposed 15 mm grid system

Key features

- Peakform : patented design for strength, stability and easier to cut
- Superlock clip: secure Main Runner connection for better alignment and easier to disconnect
- Rotary stitched: strength and extra stability


Application areas






















Healthcare / Classrooms / Meeting rooms / Individual offices

Physical data


- Material: galvanised steel
- Surface finish: baked polyester paint
- Colour: all products standard in Global White
- Other standard colours available on popular items






















































































PRELUDE 15 - UNIVERSAL PEAKFORM MAIN RUNNER & SUPERLOCK CLIP (bulb-to-bulb connection)



Item Nr.	Dimensions (mm)				Standard colours					
	length	width	height	slot centres	Global white	White RAL 9010	Silver RAL 9006	Black	Brass	Chrome
 31 40 33 A	3600	15	43	100						
 30 41 33 B	3750	15	43	156.5						
 30 43 33 B	3375	15	43	337.5						

PRELUDE 15 - XL² PEAKFORM CROSS TEES (stab system, override)



Cross Tees slotted										
 30 30 33 B	1200	15	38	300						
 30 31 33 A	1250	15	38	312.5						
 30 32 33	1000	15	38	250						
 30 30 32	1200	15	38	1						
 30 36 32	1500	15	38	2						
 30 34 32	1800	15	38	300						
 30 09 32	2400	15	38	300						
Cross Tees unslotted										
30 20 33 B	600	15	38	-						
30 21 33 A	325	15	38	-						
30 22 33	500	15	38	-						
30 05 32	550	15	38	-						
A 30 12 33	150	15	38	-						
A 30 04 33	100	15	38	-						

¹ Slots at: 300, 550, 600, 650, 900 mm

² Slots at: 150, 500, 750, 1000, 1350 mm

SUSTAINABILITY



25



A+



E1

FIRE REACTION



EEA Euroclass A1
EN 13501-1

RUS KM0 (NG)/
KM1 (G1, V1, D1, T1)
FZ 123

OTHER PERFORMANCES & FEATURES



ISO 3

30 YEAR
system
guarantee

CUSTOM OPTIONS



Colours



Dimensions

